

KOHLER[®]

KOHLER NEW ZEALAND LIMITED
 133 DIANA DRIVE, GLENFIELD AUCKLAND 0627
 PO BOX 100-146 N.S.M.C AUCKLAND NEW ZEALAND
 PHONE +64 9 980 6800

Englefield Back-to-wall & Close-coupled Toilets

BPIR Declaration

Version: A1 (12/23)

Designated building product: Class 1

Declaration

Kohler New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name	Englefield Back-to-wall & Close-coupled Toilets
Identifier	Evora / Evora II Raised Height / Milano / Valencia / Topaz / Ruby / Emerald
	(including <u>installation only</u> of Englefield Bidet Seats to compatible toilets)

Description

Floor mounted back-to-wall & close coupled toilets for installation in residential & commercial buildings.

Water conserving dual flush with WELS 4 star rating (3.5 litre average flush).

Pans & cisterns are made from white glazed vitreous china. Seats are made from highly durable UF (Urea Formaldehyde).

Supplied with a Watermark certified S trap pan connector to achieve a wide range of set outs (refer to specification sheet for each model). P trap installation with a straight pan connector (not supplied).

Evora, Evora II Raised Height & Topaz have top rear or side water inlet options. Milano has top rear water inlet only. Valencia, Ruby & Emerald have bottom water inlet (left hand or right hand).

Evora & Evora II Raised Height feature a rimless flushing platform. Milano & Valencia feature a box rim.

Evora II Raised, Milano, Valencia, Ruby & Emerald have a minimum 430mm pan height for improved sitting comfort. All toilets feature quick release seats for easier cleaning.

Scope of use

The Englefield Back-to-wall & Close-coupled Toilets are intended for use for personal sanitation in residential & commercial buildings.

All models are floor mounted & are supplied with a Watermark certified S trap pan connector to achieve a wide range of set outs (refer to specification sheet for each model). P trap installation is possible with a straight pan connector (not supplied).

Evora, Evora II Raised Height & Topaz have top rear or side water inlet options. Milano has top rear water inlet only. Valencia, Ruby & Emerald have bottom water inlet (left hand or right hand).

Conditions of use

Installation must comply with AS/NZS 3500 and AS/NZS 6400. Englefield Bidet Seats installed to compatible toilets must have High Hazard backflow prevention installed (not supplied). Please refer to the installation instructions for further information.

Must be installed by a registered plumber in accordance with our supplied instructions.

Maximum working pressure: 500kPa. If pressure exceeds 500kPa, a pressure limiting valve must be installed.

Ensure that no part of the cistern inlet hose is submerged in water (top rear water inlet only).

The pan must be firmly fixed to the floor using the supplied fixing kit.

This product is cleanable and impervious to moisture — cleaning shall be done in accordance with the supplied cleaning instructions.

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.2

Contributions to compliance

- B2.3.1(c):** Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, Englefield Back-to-wall & Close-coupled toilets have a durability of at least 5 years, when installed and maintained in accordance with our supplied instructions. Englefield Acrylic Englefield Back-to-wall & Close-coupled toilets are designed & manufactured to AS 1172.1 (Sanitary plumbing products: Water closet pans) & AS 1172.2 (Sanitary plumbing products: Flushing devices and cistern inlet and outlet valves) & are Watermark certified to these standards under Licence no. WM-022014 or WM-022642. The vitreous china material used complies with AS 1776 (Vitreous china used in sanitary appliances). Supplied flexible hoses comply with AS/NZS 3499.
- F2.3.1:** No materials used in the construction of Englefield Back-to-wall & Close-coupled toilets give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space. The vitreous china material used complies with AS 1776 (Vitreous china used in sanitary appliances).
- G1/AS1 2.1:** All requirements are satisfied per the Watermark certification to AS 1172.1 (Sanitary plumbing products: Water closet pans) under Licence no. WM-022014 or WM-022642.
- G1/AS1 2.2:** All requirements are satisfied per the Watermark certification to AS 1172.2 (Sanitary plumbing products: Flushing devices and cistern inlet and outlet valves) under Licence no. WM-022014 or WM-022642.
- G12/AS1 3.4.3(a) & 3.5.1:** The supplied flush valves have a minimum air gap of 25mm.
- G12/AS1 3.4.3(b) & 3.4.4:** [Englefield Bidet Seats installed to compatible toilets only] All supplied documentation & packaging clearly notifies to the customer & installing plumber that High Hazard backflow prevention (not supplied) must be installed.

Supporting documentation

The following additional documentation supports the above statements:

Installation instructions	Refer website.
Warranty statement	1173923-A
Care & maintenance guide	Homeowners Care Guide

For further information supporting Englefield Drop-In Baths claims refer to our website.

Contact details

Manufacture location	Thailand, China
Manufacturer name(s)	Kohler (Thailand) Public Co., Ltd. & other Kohler approved manufacturers.
Legal and trading name of importer	Kohler New Zealand Limited
Importer address for service	133 Diana Drive Auckland 0627
Importer website(s)	englefield.co.nz
Importer email	customerservicesnz@kohler.com
Importer phone number	099806800
Importer NZBN	9429037167615