

KOHLER[®]

KOHLER NEW ZEALAND LIMITED
 133 DIANA DRIVE, GLENFIELD AUCKLAND 0627
 PO BOX 100-146 N.S.M.C AUCKLAND NEW ZEALAND
 PHONE +64 9 980 6800

Englefield Wall Hung & Wall Faced Toilets

BPIR Declaration

Version: A (12/23)

Designated building product: Class 1

Declaration

Kohler New Zealand Limited has provided this declaration to satisfy the provisions of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

Product/system

Name Englefield Wall Hung & Wall Faced Toilets

Identifier Evora

Description

Wall Hung & Wall Faced toilets for installation in residential & commercial buildings.

Water conserving dual flush with WELS 4 star rating (3.5 litre average flush). Mechanical or Pneumatic flush actuation options available in both standard & low level in-wall cisterns.

Pans are made from white glazed vitreous china. Seats are made from highly durable UF (Urea Formaldehyde). In-wall cisterns are made from insulated blow moulded plastic with coated steel frames (wall hung) or brackets (wall faced). A range of finished ABS flush buttons are available in Chrome & other durable finishes for both mechanical & pneumatic options.

Evora Wall Hung features a rimless flushing platform. Evora Wall Faced features a box rim.

All toilets feature quick release seats for easier cleaning.

Scope of use

The Englefield Wall Hung & Wall Faced Toilets are intended for use for personal sanitation in residential & commercial buildings.

Standard height in-wall cisterns are installed into 90mm wall cavities. Low level in-wall cisterns require a 150mm wall cavities.

Evora Wall Hung is supplied with a Watermark certified pan connector for S trap installation through the floor of the wall cavity. Evora Wall faced is supplied with a Watermark certified pan connector for S trap at a fixed set out position in front of the wall. P trap installations are possible for both Wall Hung & Wall Faced with a straight pan connector (not supplied).

Conditions of use

Installation must comply with AS/NZS 3500 and AS/NZS 6400.

Must be installed by a registered plumber in accordance with our supplied instructions.

Maximum working pressure: 500kPa. If pressure exceeds 500kPa, a pressure limiting valve must be installed.

The Wall Faced pan must be firmly fixed to the floor using the supplied fixing kit.

This product is cleanable and impervious to moisture — cleaning shall be done in accordance with the supplied cleaning instructions.

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies — G12.3.2

Contributions to compliance

B2.3.1(c): Per B2/AS1, Durability Requirements of Nominated Building Elements for Plumbing Fixtures, Englefield Wall Hung & Wall Faced pans have a durability of at least 5 years (& have a warranty of 10 years), when installed and maintained in accordance with our supplied instructions. Englefield Wall Hung & Wall Faced in-wall cisterns have a durability of at least 15 years, when installed and maintained in accordance with our supplied instructions. Englefield Wall Hung & Wall Faced toilets are designed & manufactured to AS 1172.1 (Sanitary plumbing products: Water closet pans) & AS 1172.2 (Sanitary plumbing products: Flushing devices and cistern inlet and outlet valves) & are Watermark certified to these standards under Licence no. WM-022032 & WM-022642. The vitreous china material used complies with AS 1776 (Vitreous china used in sanitary appliances). Supplied flexible hoses comply with AS/NZS 3499.

- F2.3.1:** No materials used in the construction of Englefield Wall Hung & Wall Faced toilets give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space. The vitreous china used complies with AS 1776 (Vitreous china used in sanitary appliances).
- G1/AS1 2.1:** All requirements are satisfied per the Watermark certification to AS 1172.1 (Sanitary plumbing products: Water closet pans) under Licence no. WM-022642.
- G1/AS1 2.2:** All requirements are satisfied per the Watermark certification to AS 1172.2 (Sanitary plumbing products: Flushing devices and cistern inlet and outlet valves) under Licence no. WM-022032.
- G12/AS1 3.4.3(a) & 3.5.1:** The supplied flush valves have a minimum air gap of 25mm.

Supporting documentation

The following additional documentation supports the above statements:

Installation instructions	Refer website.
Warranty statement	1173923-A
Care & maintenance guide	Homeowners Care Guide

For further information supporting Englefield WH & WF toilets claims refer to our website.

Contact details

Manufacture location	China
Manufacturer name(s)	Changzhou Kohler Kitchen & Bath Ltd. & other Kohler approved manufacturers.
Legal and trading name of importer	Kohler New Zealand Limited
Importer address for service	133 Diana Drive Auckland 0627
Importer website(s)	englefield.co.nz
Importer email	customerservicesnz@kohler.com
Importer phone number	099806800
Importer NZBN	9429037167615